

## PRIMARY & SECONDARY SUPPORT SOLUTION FOR M&E INSTALLATIONS



The range consists of three pre-determined lengths of wire for the installation of primary and secondary installations. Safe Working Loads:

- Green 10kg
- Silver 35kg

Available in drops to suit fittings with:

- 50-100mm width
- 150-200mm width
- 300-400mm width

The system is designed to be used in conjunction with Rize, Zip-Lock, Con-Lock, Dec-Lock, Shot-Lock & Uni-Lock.

- Reduces the use of studding and channel
- One fixing point per drop
- Height can be adjusted at installation and not at fixing
- Can be fixed to installation at ground level

## APPLICATION

Suitable for primary and secondary support for suspending:

- Lighting fittings
- Heat Panels
- Plenum boxes
- Basket, ladder and tray



- ◇ Plastic protection sleeve preventing wire on wire
- ◇ High tensile Galvanised wire 1960n/mm<sup>2</sup> grade 7x7 construction
- ◇ BSEN 12385 Standard

**10kg SWL**

PRODUCT CODE	DESCRIPTION	SAFE WORKING LOAD
LUMG 50-100	230mm Luma-Lock Support System 10pcs per pack	10kg SWL
LUMG 150-200	300mm Luma-Lock Support System 10pcs per pack	10kg SWL
LUMG 300-400	460mm Luma-Lock Support System 10pcs per pack	10kg SWL

**35kg SWL**

PRODUCT CODE	DESCRIPTION	SAFE WORKING LOAD
LUM 50-100	230mm Luma-Lock Support System 10pcs per pack	35kg SWL
LUM 150-200	300mm Luma-Lock Support System 10pcs per pack	35kg SWL
LUM 300-400	460mm Luma-Lock Support System 10pcs per pack	35kg SWL

**INSTALLATION METHOD**

- The attachment of the Luma-Lock system can be done at ground level
- Attach the two toggles through the rear of the system being suspended
- By inverting the toggle parallel to the wire the toggle will swing through 90 degrees
- Pass the free end of the wire from your top suspension through the plastic protected loop and adjust the height and level required using the clip
- Legs should not exceed 60 degrees.

